

Federal Communications Commission

§21.117

which will be provided by Cornell University. Applicants who choose to transmit information electronically should e-mail to: prcz@naic.edu

(1) The notification to the Interference Office, Arecibo Observatory shall be made prior to, or simultaneously with, the filing of the application with the Commission. The notification shall state the geographical coordinates of the antenna (NAD-83 datum), antenna height above ground, ground elevation at the antenna, antenna directivity and gain, proposed frequency and FCC Rule Part, type of emission, effective radiated power, and whether the proposed use is itinerant. Generally, submission of the information in the technical portion of the FCC license application is adequate notification. In addition, the applicant shall indicate in its application to the Commission the date notification was made to the Arecibo Observatory.

(2) After receipt of such applications, the Commission will allow the Arecibo Observatory a period of 20 days for comments or objections in response to the notification indicated. The applicant will be required to make reasonable efforts in order to resolve or mitigate any potential interference problem with the Arecibo Observatory and to file either an amendment to the application or a modification application, as appropriate. If the Commission determines that an applicant has satisfied its responsibility to make reasonable efforts to protect the Observatory from interference, its application may be granted.

(3) The provisions of this paragraph do not apply to operations that transmit on frequencies above 15 GHz.

[44 FR 60534, Oct. 19, 1979, as amended at 44 FR 77167, Dec. 31, 1979; 50 FR 39001, Sept. 26, 1985; 52 FR 37783, Oct. 9, 1987; 58 FR 44894, Aug. 25, 1993; 61 FR 8477, Mar. 5, 1996; 62 FR 55530, Oct. 27, 1997]

§§ 21.114–21.115 [Reserved]

§21.116 Topographical data.

Determining the location and height above sea level of the antenna site, the elevation or contour intervals shall be taken from United States Geological Survey Topographic Quadrangle Maps, United States Army Corps of Engineers

maps or Tennessee Valley Authority maps, whichever is the latest, for all areas for which such maps are available. If such maps are not published for the area in question, the next best topographic information should be used. Topographic data may sometimes be obtained from State and municipal agencies. Data from Sectional Aeronautical Charts (including bench marks) or railroad depot elevations and highway elevations from road maps may be used where no better information is available. In cases where limited topographic data is available, use may be made of an altimeter in a car driven along roads extending generally radially from the transmitter site. If it appears necessary, additional data may be requested. United States Geological Survey Topographic Quadrangle Maps may be obtained from the Department of the Interior, Geological Survey, Washington, DC 20242. Sectional Aeronautical Charts are available from the Department of Commerce, Coast and Geodetic Survey, Washington, DC 20230.

[44 FR 60534, Oct. 19, 1979, as amended at 52 FR 37783, Oct. 9, 1987]

§21.117 Transmitter location.

(a) The applicant shall determine, prior to filing an application for a radio station authorization, that the antenna site specified therein is adequate to render the service proposed. In cases of questionable antenna locations, it is desirable to conduct propagation tests to indicate the field intensity which may be expected in the principal areas or at the fixed points of communication to be served, particularly where severe shadow problems may be expected. In considering applications proposing the use of such locations, the Commission may require site survey tests to be made pursuant to a developmental authorization in the particular service concerned. In such cases, propagation tests should be conducted in accordance with recognized engineering methods and should be made with a transmitting antenna simulating, as near as possible, the proposed antenna installation. Full data obtained from such surveys and its analysis, including a description of the methods used and the name, address

§21.118

and qualifications of the engineer making the survey, must be supplied to the Commission.

(b) The owner of the antenna structure should locate and construct such structure as to avoid making them hazardous to air navigation. (See part 17 of this chapter for provisions relating to antenna structures.) Such installation shall be maintained in good structural condition together with any required painting or lighting.

[44 FR 60534, Oct. 19, 1979, as amended at 61 FR 4365, Feb. 6, 1996]

§21.118 Transmitter construction and installation.

(a) The equipment at the operating and transmitting positions shall be so installed and protected that it is not accessible to, or capable of being operated by, persons other than those duly authorized by the licensee.

(b) In any case where the maximum modulating frequency of a transmitter is prescribed by the Commission, the transmitter shall be equipped with a low-pass or band-pass modulation filter of suitable performance characteristics. In those cases where a modulation limiter is employed, the modulation filter shall be installed between the transmitter stage in which limiting is effected and the modulated stage of the transmitter.

(c) Each transmitter employed in these services shall be equipped with an appropriately labeled pilot lamp or meter which will provide continuous visual indication at the transmitter when its control circuits have been placed in a condition to activate the transmitter. Such requirement will not be applicable to MDS response stations or MDS booster stations authorized pursuant to §21.913(e). In addition, facilities shall be provided at each transmitter to permit the transmitter to be turned on and off independently of any remote control circuits associated therewith.

(d) [Reserved]

(e) At each transmitter control point the following facilities shall be installed:

(1) A carrier operated device which will provide continuous visual indication when the transmitter is radiating, or, in lieu thereof, a pilot lamp or

47 CFR Ch. I (10–1–01 Edition)

meter which will provide continuous visual indication when the transmitter control circuits have been placed in a condition to activate the transmitter.

(2) Facilities which will permit the operator to turn transmitter carrier on and off at will.

(f) Transmitter control circuits from any control point shall be so installed that grounding or shorting any line in the control circuit will not cause the transmitter to radiate: *Provided, however*, That this provision shall not be applicable to control circuits of stations which normally operate with continuous radiation or to control circuits which are under the effective operational control of responsible operating personnel 24 hours per day.

[44 FR 60534, Oct. 19, 1979, as amended at 52 FR 37783, Oct. 9, 1987; 63 FR 65101, Nov. 25, 1998]

§21.119 [Reserved]

§21.120 Authorization of transmitters.

(a) Except for transmitters used at developmental stations, each transmitter shall be a type which has been certificated by the Commission for use under the applicable rules of this part.

(b) Any manufacturer of a transmitter to be produced for use under the rules of this part may request certification by following the applicable procedures set forth in part 2 of this chapter. Type accepted and notified transmitters are included in the Commission's Radio Equipment List.

(c) Certification for an individual transmitter may also be requested by an applicant for a station authorization, pursuant to the procedures set forth in part 2 of this chapter.

[44 FR 60534, Oct. 19, 1979, as amended at 49 FR 3999, Feb. 1, 1984; 50 FR 7340, Feb. 22, 1985; 58 FR 49226, Sept. 22, 1993; 59 FR 19645, Apr. 25, 1994; 61 FR 26676, May 28, 1996; 63 FR 36603, July 7, 1998]

§21.121 [Reserved]

§21.122 Microwave digital modulation.

(a) Microwave transmitters employing digital modulation techniques and operating below 15 GHz shall, with appropriate multiplex equipment, comply with the following additional requirement: The bit rate, in bits per second,